



NOTES:

1. MATERIALS:  
.RECEPTACLE : BRASS
2. PLATING:  
.RECEPTACLE : BRASS Ni/Au  
.OVER SUBSTRATE PLATED 80~120  $\mu$ " Nickel  
. 2  $\mu$ " Au PLATED.
3. DETENT A, THE INSERT FORCE IS 0.3~0.7Kg.(BEFORE PLATING)
4. DETENT A, THE INSERT FORCE IS 0.5~1.2Kg.(AFTER PLATING)
5. Harmful material control please follow DOC. NO."DQ03050"
6. The original P/N: PR-2W1-A10 (原物料料号: PR-2W1-A10)

DRAWN (设计)	linyushou	SCALE (比例)	1 : 1	UNIT (单位)	mm	DRAWING NO. (图号)	PR-2W1-A05S
CHECKED (确认)		SHEET (页数)	1 of 1	PROJECT (视图)		TITLE (品名)	Plunger
APPROVED (核准)		DATE (日期)	2014.05.06	VER. (版本)	A.0		
THE UNMARKED TOLERANCE ARE AS BELOW : (未标记的公差)							
LENGTH (尺寸)		ANGLE (角度)					
0~6.0	$\pm 0.05$ mm	0.0	$\pm 2.0^\circ$				
>6~30	$\pm 0.10$ mm	0.0	$\pm 1.0^\circ$				
>30~120	$\pm 0.15$ mm	0.00	$\pm 0.50^\circ$				
				C.C.P. (DG) CONTACT PROBES CO.,LTD. 东莞中探探针有限公司			
The information in this document is property of C.C.P company and should not be copied or reproduced in any other way, without written permission.							